

10/551425

JC12 Rec'd PCT/PTC 03 OCT 2005

PATENT APPLICATION

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re the Application of

Jean-Jacques YON et al.

Attn: PCT Branch

Application No. New U.S. National Stage of PCT/FR04/000942

Filed: October 3, 2005

Docket No.: 125487

For: THERMAL ELECTROMAGNETIC RADIATION DETECTOR WITH
ALVEOLATE STRUCTURE


**TRANSLATION OF THE ANNEXES TO THE
INTERNATIONAL PRELIMINARY EXAMINATION REPORT**

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:

Attached hereto is a translation of the annexes to the International Preliminary Examination Report (Form PCT/IPEA/409). The attached translated material replaces the claims.

Respectfully submitted,


William P. Berridge
Registration No. 30,024

Eric D. Morehouse
Registration No. 38,565

WPB:EDM/cqc

Date: October 3, 2005

OLIFF & BERRIDGE, PLC
P.O. Box 19928
Alexandria, Virginia 22320
Telephone: (703) 836-6400

DEPOSIT ACCOUNT USE AUTHORIZATION Please grant any extension necessary for entry; Charge any fee due to our Deposit Account No. 15-0461
--

Claims

- 5 1. Thermal electromagnetic radiation detector comprising an absorbent membrane (1) fixed in suspension onto a front face of a substrate (2), in a direction substantially parallel to the substrate (2), by support means thermally insulating the membrane (1) from the substrate (2), detector characterized in that the support means comprise at least one alveolate structure arranged substantially perpendicularly to the front face of the substrate (2) and to the plane of the membrane (1).
- 10
2. Detector according to claim 1, characterized in that the alveolate structure is arranged between the absorbent membrane (1) and the substrate (2), along one edge of the absorbent membrane (1).
- 15
3. Detector according to one of the claims 1 and 2, characterized in that the support means comprise at least one arm (3) fixedly secured to the absorbent membrane (1), each alveolate structure being respectively arranged between the corresponding arm (3) and the substrate (2).
- 20
4. Detector according to claim 3, characterized in that the alveolate structure is in contact with an arm (3) by a single bearing point (5).
- 25
5. Detector according to any one of the claims 1 to 4, characterized in that the alveolate structure is formed by a wall presenting a plurality of transverse apertures.

6. Detector according to claim 5, characterized in that the wall comprises a plurality of superposed thin layers (6) separated by spacers.

5 7. Detector according to claim 6, characterized in that the spacers are formed by partitions (7) perpendicular to the substrate (2).

8. Detector according to claim 6, characterized in that the spacers are formed by hollow cylinders (8) arranged perpendicularly to the substrate (2).

10 9. Detector according to claim 5, characterized in that the wall comprises at least two superposed rows of arcades (9) formed by thin layers, a first row of arcades (9) being arranged on the front face of the substrate (2), an arcade (9) of another row being arranged on the top parts of two adjacent arcades (9) of the bottom row.

15

10. Detector according to any one of the claims 1 to 4, characterized in that the alveolate structure comprises a porous pad (10).

20